

USA Type Quick Coupler

INDUSTRIAL TYPE [MILTON TYPE]

FEATURES

- Accepts 1/4 INDUSTRIAL Type plugs
- Heavy-duty,high-quality design
- Deep knurled socket sleeve for positive gripping
- Proven and positive connection using ball-locjing mechanism

SPECIFICATIONS

- Maximum Working Pressure: 150 PSI
- Temperature Range: -40° F ~225° F (-20 °C~107°C)
- Air Flow: 35 SCFM at 100 PSIG inlet with 10 PSIG pressure drop



| Model | Size |
|---------|------------------------|
| PU1-2SF | 1/4" NPT FEMALE THREAD |
| PU1-3SF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|---------|------------------------|
| PU1-2PF | 1/4" NPT FEMALE THREAD |
| PU1-3PF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|---------|------------------------|
| PU3-2SF | 1/4" NPT FEMALE THREAD |
| PU3-3SF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|---------|------------------------|
| PU3-2PF | 1/4" NPT FEMALE THREAD |
| PU3-3PF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|---------|----------------|
| PU1-2SH | 1/4" HOSE BARB |
| PU1-3SH | 3/8" HOSE BARB |



| Model | Size |
|---------|----------------|
| PU1-2PH | 1/4" HOSE BARB |
| PU1-3PH | 3/8" HOSE BARB |



| Model | Size |
|---------|----------------|
| PU3-2SH | 1/4" HOSE BARB |
| PU3-3SH | 3/8" HOSE BARB |



| Model | Size |
|---------|----------------|
| PU3-2PH | 1/4" HOSE BARB |
| PU3-3PH | 3/8" HOSE BARB |



| Model | Size |
|---------|----------------------|
| PU1-2SM | 1/4" NPT MALE THREAD |
| PU1-3SM | 3/8" NPT MALE THREAD |



| Model | Size |
|---------|----------------------|
| PU1-2PM | 1/4" NPT MALE THREAD |
| PU1-3PM | 3/8" NPT MALE THREAD |



| Model | Size |
|---------|----------------------|
| PU3-2SM | 1/4" NPT MALE THREAD |
| PU3-3SM | 3/8" NPT MALE THREAD |



| Model | Size |
|---------|----------------------|
| PU3-2PM | 1/4" NPT MALE THREAD |
| PU3-3PM | 3/8" NPT MALE THREAD |

USA Type Quick Coupler

AUTOMOTIVE TYPE [TRUFLATE TYPE]

FEATURES

- Accepts 1/4 AUTOMOTIVE Type plugs
- Heavy-duty,high-quality design
- Deep knurled socket sleeve for positive gripping
- Proven and positive connection using ball-locjing mechanism

SPECIFICATIONS

- Maximum Working Pressure: 150 PSI
- Temperature Range: -40° F ~225° F (-20 °C~107°C)
- Air Flow: 35 SCFM at 100 PSIG inlet with 10 PSIG pressure drop



| Model | Size |
|---------|------------------------|
| PU4-2SF | 1/4" NPT FEMALE THREAD |
| PU4-3SF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|---------|------------------------|
| PU4-2PF | 1/4" NPT FEMALE THREAD |
| PU4-3PF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|---------|------------------------|
| PU5-2SF | 1/4" NPT FEMALE THREAD |
| PU5-3SF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|---------|------------------------|
| PU5-2PF | 1/4" NPT FEMALE THREAD |
| PU5-3PF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|---------|----------------|
| PU4-2SH | 1/4" HOSE BARB |
| PU4-3SH | 3/8" HOSE BARB |



| Model | Size |
|---------|----------------|
| PU4-2PH | 1/4" HOSE BARB |
| PU4-3PH | 3/8" HOSE BARB |



| Model | Size |
|---------|----------------|
| PU5-2SH | 1/4" HOSE BARB |
| PU5-3SH | 3/8" HOSE BARB |



| Model | Size |
|---------|----------------|
| PU5-2PH | 1/4" HOSE BARB |
| PU5-3PH | 3/8" HOSE BARB |



| Model | Size |
|---------|----------------------|
| PU4-2SM | 1/4" NPT MALE THREAD |
| PU4-3SM | 3/8" NPT MALE THREAD |



| Model | Size |
|---------|----------------------|
| PU4-2PM | 1/4" NPT MALE THREAD |
| PU4-3PM | 3/8" NPT MALE THREAD |



| Model | Size |
|---------|----------------------|
| PU5-2SM | 1/4" NPT MALE THREAD |
| PU5-3SM | 3/8" NPT MALE THREAD |



| Model | Size |
|---------|----------------------|
| PU5-2PM | 1/4" NPT MALE THREAD |
| PU5-3PM | 3/8" NPT MALE THREAD |

USA Type Quick Coupler

ARO TYPE

FEATURES

- Accepts 1/4 ARO Type plugs
- Heavy-duty,high-quality design
- Deep knurled socket sleeve for positive gripping
- Proven and positive connection using ball-locjing mechanism

SPECIFICATIONS

- Maximum Working Pressure: 150 PSI
- Temperature Range: -40° F ~225° F (-20 °C~107°C)
- Air Flow: 35 SCFM at 100 PSIG inlet with 10 PSIG pressure drop

★ ONE TOUCH TYPE (PU11 Series)



| Model | Size |
|----------|------------------------|
| PU11-2SF | 1/4" NPT FEMALE THREAD |
| PU11-3SF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|----------|------------------------|
| PU11-2PF | 1/4" NPT FEMALE THREAD |
| PU11-3PF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|----------|----------------|
| PU11-2SH | 1/4" HOSE BARB |
| PU11-3SH | 3/8" HOSE BARB |



| Model | Size |
|----------|----------------|
| PU11-2PH | 1/4" HOSE BARB |
| PU11-3PH | 3/8" HOSE BARB |



| Model | Size |
|----------|----------------------|
| PU11-2SM | 1/4" NPT MALE THREAD |
| PU11-3SM | 3/8" NPT MALE THREAD |



| Model | Size |
|----------|----------------------|
| PU11-2PM | 1/4" NPT MALE THREAD |
| PU11-3PM | 3/8" NPT MALE THREAD |

★ TWO TOUCH TYPE (PU6 Series)



| Model | Size |
|---------|------------------------|
| PU6-2SF | 1/4" NPT FEMALE THREAD |
| PU6-2SF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|---------|------------------------|
| PU6-2PF | 1/4" NPT FEMALE THREAD |
| PU6-3PF | 3/8" NPT FEMALE THREAD |



| Model | Size |
|---------|----------------|
| PU6-2SH | 1/4" HOSE BARB |
| PU6-3SH | 3/8" HOSE BARB |



| Model | Size |
|---------|----------------|
| PU6-2PH | 1/4" HOSE BARB |
| PU6-3PH | 3/8" HOSE BARB |



| Model | Size |
|---------|----------------------|
| PU6-2SM | 1/4" NPT MALE THREAD |
| PU6-3SM | 3/8" NPT MALE THREAD |



| Model | Size |
|---------|----------------------|
| PU6-2PM | 1/4" NPT MALE THREAD |
| PU6-3PM | 3/8" NPT MALE THREAD |